

Service Manual

JS330 from machine no. 712501

JS450 from machine no. 714501

JS460

from machine no. 714550

PUBLISHED BY THE
TECHNICAL PUBLICATIONS DEPARTMENT
OF JCB SERVICE: ©
WORLD PARTS CENTRE
UTTOXETER, STAFFORDSHIRE, ST14 7BS,
ENGLAND
Tel. ROCESTER (01889) 590312
PRINTED IN ENGLAND

Publication No. 9803/6420 Issue 3

General Information	1
Care & Safety	2
Routine Maintenance	3
Attachments	A
Body & Framework	В
Electrics	С
Hydraulics	E
Transmission	F
Brakes	G
Track & Running Gear	J
Engine	K

Introduction

This publication is designed for the benefit of JCB Distributor Service Engineers who are receiving, or have received, training by JCB Technical Training Department.

These personnel should have a sound knowledge of workshop practice, safety procedures, and general techniques associated with the maintenance and repair of hydraulic earthmoving equipment.

Renewal of oil seals, gaskets, etc., and any component showing obvious signs of wear or damage is expected as a matter of course. It is expected that components will be cleaned and lubricated where appropriate, and that any opened hose or pipe connections will be blanked to prevent excessive loss of hydraulic fluid and ingress of dirt. Finally, please remember above all else **SAFETY MUST COME FIRST!**

The manual is compiled in sections, the first three are numbered and contain information as follows:

- 1 = General Information includes torque settings and service tools.
- 2 = Care & Safety includes warnings and cautions pertinent to aspects of workshop procedures etc.
- 3 = Routine Maintenance includes service schedules and recommended lubricants for the whole machine.

The remaining sections are alphabetically coded and deal with Dismantling, Overhaul etc. of specific components, for example:

- A = Attachments
- B = Body & Framework ...etc

The page numbering in each alphabetically coded section is not continuous. This allows for the insertion of new items in later issues of the manual.

Section contents, technical data, circuit descriptions, operation descriptions etc. are inserted at the beginning of each alphabetically coded section.

All sections are listed on the front cover; tabbed divider cards align directly with individual sections on the front cover for rapid reference.

Where a torque setting is given as a single figure it may be varied by plus or minus 3%. Torque figures indicated are for dry threads, hence for lubricated threads may be reduced by one third.

'Left Hand' and 'Right Hand' are as viewed from the rear of the machine facing forwards.

Note: In this manual the term 'swing' may sometimes be used in place of 'slew' and the term 'arm' may sometimes be used in place of 'dipper'.

9803/6420 Issue 1

:

Contents	Page No.
Bolt and Nut Torque Specification	ns 1 - 1
Torque Settings	1 - 2
Service Tools Section B - Body & Frame Section C - Electrics Section E - Hydraulics	work 3 - 1 4 - 1 5 - 1
Sealing and Retaining Compound	ds 6 - 1

9803/6420 Issue 2*